

System 7100 – Data Acquisition System

FEATURES

- Stable, accurate, low-noise signal conditioning
- Individual input cards for strain gage and strain-gage based transducers, thermocouples, sensors with high level voltage outputs, and LVDTs
- Electronically selectable, built-in bridge completion for 120, 350, and 1000 Ohm strain gages
- Scalable synchronized system (using multiple scanners)
- Maximum scan rate of 2000 samples per second (Radix-10).
- Self-calibration traceable to NIST standard
- Simultaneous sampling with anti-aliasing filter and analog-to-digital conversion for each channel
- Selectable digital filtering of measurement signals
- High-speed Ethernet network interface with DHCP addressing

DESCRIPTION

Micro-Measurements System 7100 builds upon the years of experience gained since the introduction of Systems 4000, 5000, 6000 and 7000 by continuing to provide a complete hardware/software approach to data acquisition, reduction, and presentation for strain gages and related sensors for stress analysis testing.

System 7100 hardware is designed to incorporate all the features required for precision strain measurement in a high channel density enclosure. Strain gages, strain-gage based transducers, thermocouples, LVDTs, and other sensors with high level voltage outputs can be intermixed in groups of eight (8) by choosing the appropriate sensor card for up to 128 channels in a 5U height, 19-inch rack mountable scanner (7100-128-SM). A 32-channel scanner is also available (7100-32-SM). The Ethernet interface with DHCP addressing allows flexible positioning of scanners, and multiple scanners can easily be synchronized using a single sync cable (maximum length 100 feet (30m)).

System 7100 is a high performance data acquisition. Each sensor channel employs a 24-bit analog-to-digital converter. Scan rates up to 2000 updates per second are available for simultaneous reading of all sensor inputs.



A combination of analog and flexible Finite Impulse Response (FIR) filters are available to provide adequate anti-alias filtering at all scanning rates. Each scanner module has high-capacity non-volatile data storage capability. Electronically selectable bridge completion resistors allow the user to choose between 120, 350, and 1000 Ohm strain gages through software selection.

Several design features are provided to reduce total cost of ownership. System 7000 is capable of self-calibration with a removable calibration reference (7100-SM-VC). Calibration can be performed anywhere and there is no need to return the entire system to the factory for calibration. Downtime while waiting for calibration is essentially eliminated. Input connectors are RJ45 type (except for the TC card) and assembly time is fast using simple cable crimping tools. Individual scanners can be separated and located near sensors to reduce sensor signal loss and cabling costs.

System 7100 – Data Acquisition System

MODEL 7100-128-SM - 128-CHANNELS SCANNER SPECIFICATIONS

Model 7100-128-SM Scanner houses and retains up to 16 input cards, regulates power to the cards, establishes and maintains communication between the Ethernet interface and the input cards, synchronizes the analog-to-digital converters in the system, and provides visual status information to the operator.

Parameter	Value
Capacity	Up to 16 Input Cards, 8 channels each, maximum 128 channels per scanner
Installation	Rack-mount (19-inch) or bench-top
Front panel	Incorporates power switch and four status LEDs
Input Power	11-32 VDC, 40A max.
Power Indication	Green LED (illuminated when power is on)
Ethernet Interface	802.3z Gigabit Ethernet
Processor	Cortex-A8, 32 bit, RISC
Memory	512MB DDR3
System Synchronization	
Connections	Sync In, Sync Out
Topology	Daisy-chain
Cable Connection	RJ45, Category 5
Max. Distance	100 ft (30m) between scanners
System Calibration Reference	
Drift	1.9 ppm/°C $\pm 0.6 \mu\text{V}/^\circ\text{C}$ typical, 9.4 ppm/°C $\pm 2.1 \mu\text{V}/^\circ\text{C}$ maximum
Resolution	150 μV nominal
Voltage Range	$\pm 5\text{V}$
Dimensions	9.25 H x 17.3 W x 13.8 D inches (235 x 440 x 351 mm)
Weight	18.2 lb (8.25 kg)

System 7100 – Data Acquisition System


MODEL 7100-32-SM - 32-CHANNELS SCANNER SPECIFICATIONS



Model 7100-32-SM Scanner houses and retains up to 4 input cards, regulates power to the cards, establishes and maintains communication between the Ethernet interface and the input cards, synchronizes the analog-to-digital converters in the system, and provides visual status information to the operator.

Parameter	Value
Capacity	Up to 4 Input Cards, 8 channels each, maximum 32 channels per scanner
Installation	Bench-top
Front panel	Incorporates power switch and four status LEDs
Input Power	11–32 VDC, 12A max
Power Indication	Green LED (illuminated when power is on)
Ethernet Interface	802.3z Gigabit Ethernet
Processor	Cortex-A8, 32 bit, RISC
Memory	512MB DDR3
System Synchronization	
Connections	Sync In, Sync Out
Topology	Daisy-chain
Cable Connection	RJ45, Category 5
Max. Distance	100 ft (30m) between scanners
System Calibration Reference	
Drift	1.9 ppm/°C ±0.6 µV/°C typical, 9.4 ppm/°C ±2.1 µV/°C maximum
Resolution	150 µV nominal
Voltage Range	±5V
Dimensions	9.1 H x 5.9 W x 13.9 D inches (231 x 150 x 352 mm)
Weight	10.1 lb (4.6 kg)

System 7100 – Data Acquisition System

MODEL 7100-8-SG - STRAIN GAGE INPUT CARDS

Model 7100-8-SG Strain Gage Input Cards accomplish bridge excitation, bridge completion, shunt calibration, and signal conditioning for eight quarter, half, and full bridges.


Parameter	Value		
Channels	Eight per card		
Inputs	Software selectable for S+/S-, VCAL+/VCAL-, or excitation		
Strain Gage	120 Ω, 350 Ω, 1000 Ω quarter-bridges; 60 Ω to 5000 Ω half- and full-bridges		
Sample rate	2000, 1000, 500, 200, 100, and 10 samples/ second		
Input Impedance	220 MΩ nominal each input		
Source Current	±5 nA per volt excitation		
Measurement Range and Resolution			
Resolution	0.5 µε (GF=2)		
Range	Total range depends on excitation setting (see table):		
	Excitation (Volts)	Measuring Range	
		µε @ GF=2	mV/V
	0	77,500*	19*
	0.25	310,000	155
	0.5	155,000	77
	0.75	103,000	51
	1	77,000	38
	2	38,000	19
	3	25,000	12
	4	77,000	38
	5	62,000	31
	6	51,000	25
	7	44,000	22
	8	38,000	19
	9	34,000	17
10	31,000	15	
Input Connector	RJ45		
Amplifier			
Zero Temperature Stability	±1 µV/°C RTI, after 60-minute warm-up		
DC Gain Accuracy and Stability	±0.1%; ±50 ppm/°C (1 year without periodic VCAL)		
Analog Input (Including Full-Scale Balance)			
Low Range	±38 mV		
High Range	±155 mV		
Linearity	±0.02% of Full Scale		
Common-Mode Rejection	>90 dB (DC to 60 Hz)		
Common-Mode Voltage Range	±12V typical		

*Based on 1 volt excitation

System 7100 – Data Acquisition System

MODEL 7100-8-SG - STRAIN GAGE INPUT CARDS (cont.)	
Parameter	Value
Balance	
Type	Software (mathematical)
Range	Full ADC range
Excitation	
Selection	Firmware controlled per channel
Resolution	3 mV
Accuracy	±10 mV typical (Firmware measures excitation variations during arming process)
Current	50 mA max. per channel; Over-current limited; Over-current indication
Load Regulation	<0.05% of full scale for 10% to 100% of full scale load with remote sense
Temperature Stability	±10 ppm/°C
Quarter-Bridge Completion	
Selection	Firmware controlled
Accuracy and Drift 120Ω and 350Ω: 1 kΩ:	±0.01%, 5 ppm/°C max. ±0.01%, 4.5 ppm/°C max. (socketed)
Shunt Calibration	
Selection	Firmware controlled
Configuration Internal QB: External:	P- to D120, P- to D350, P- to D1000 Switched shunt at Input Connector (Ra, Rb)
Standard Factory Installed resistors values (Simulates 10,000 µε@GF=2.0)	5,940 Ω ± 0.1%: shunts P- to D120 17,325 Ω ± 0.1%: shunts P- to D350 49,500 Ω ± 0.1%: shunts P- to D1000 17,325 Ω ± 0.1%: external shunt Ra to Rb
Sockets	Tin-plated
System Calibration	Firmware controlled
Calibration voltage	Supplied by Model 7100-SM-VC voltage calibration card
Type	Ten point calibration, 100 samples per point
Size	6.5 H x 1.0 W x 12.5 D in (165 x 25.4 x 318 mm)
Weight	0.9 lb (0.4 kg)

System 7100 – Data Acquisition System


MODEL 7100-8-TC - THERMOCOUPLE INPUT CARD

Model 7100-8-TC Thermocouple Input Card is to perform signal conditioning and cold-junction compensation.

Parameter	Value
Channels	Eight per card
Inputs	
Supported Thermocouple Types	J, K, T, E, N, R, S, B
Cold-junction compensation:	Software-selectable
Open-sensor detection	
Input Impedance	220 M Ω nominal each input
Input Connectors	mini-TC
Sample rate	2000, 1000, 500, 200, 100, and 10 samples/second
Amplifier	
Zero Temperature Stability	$\pm 2 \mu\text{V}/^\circ\text{C}$ RTI, $\pm 10 \mu\text{V}/^\circ\text{C}$ RTO, after 60-minute warm-up
DC Gain Accuracy and Stability	$\pm 0.1\%$; $\pm 30 \text{ ppm}/^\circ\text{C}$
Linearity	$\pm 0.02\%$ of Full Scale
Common Mode Rejection (DC to 60 Hz)	>90 dB
Common Mode Voltage Range	$\pm 12\text{V}$ typical
Measurement Range and Resolution	
Range:	$\pm 77.5 \text{ mV}$
Resolution:	1°C minimum
Accuracy	$\pm 2^\circ\text{C}$
Size	6.5 H x 1.0 W x 12.5 D in (165 x 25.4 x 318 mm)
Weight:	0.9 lb (0.4 kg)

System 7100 – Data Acquisition System

MODEL 7100-8-HL - HIGH LEVEL INPUT CARD



Model 7100-8-HL High Level Input Card is used to perform signal conditioning and excitation for high level ($\pm 10V$) inputs.

Parameter	Value
Channels	Eight per card
Inputs	Differential
Input Impedance	220 M Ω nominal each input
Input Bias Current	± 0.5 nA typical (± 2 nA max.)
Input Connector	RJ45
Sample rate	2000, 1000, 500, 200, 100, and 10 samples/second
Amplifier	
Zero Temperature Stability	± 2 $\mu V/^{\circ}C$ RTI, typical, ± 10 $\mu V/^{\circ}C$ RTO, after 60-minute warm-up
DC Gain Accuracy and Stability	$\pm 0.1\%$; ± 30 ppm / $^{\circ}C$
Linearity	$\pm 0.02\%$ of Full Scale
Common-Mode Rejection (DC to 60 Hz)	>90 dB
Common-Mode Voltage Range	± 12 V typical
Measurement Ranges and Resolution	Range: Resolution:
	± 10 V 100 μV effective
Excitation	Firmware controlled settable per channel
Unipolar Mode	
Range	0 to +11.997 VDC
Accuracy	± 10 mV typical
Current	50 mA max. Over-current/over-temperature protected
Load Regulation	<0.05% of full scale (unipolar mode) for a load variation of 10% to 100% of full scale loads (with remote sense)
Temperature Stability	Better than ± 30 ppm/ $^{\circ}C$
Bipolar Mode	
Range	± 12 VDC (24 VDC total)
Accuracy	$\pm 5\%$ of full scale
Size	6.5 H x 1.0 W x 12.5 D in (165 x 25.4 x 318 mm)
Weight:	0.9 lb (0.4 kg)

System 7100 – Data Acquisition System

MODEL 7100-8-LVDT - LVDT CARD	
	Model 7100-8-LVDT is used to perform signal conditioning, polarity demodulation and AC excitation for Transformer-type transducers.
Parameter	Value
Channels	Eight per card
Inputs	Six-, five-, four- and three-wire transducers
Input Impedance	220 M Ω nominal each input with 0.001 μ F parallel to both inputs
Input Bias Current	± 0.5 nA typical (± 2 nA max.)
Input Connector	RJ45
Sample rate	2000, 1000, 500, 200, 100, and 10 samples/second
Amplifier	
Zero Temperature Stability	± 2 μ V/ $^{\circ}$ C RTI, typical, ± 10 μ V/ $^{\circ}$ C RTO, after 60-minute warm-up
DC Gain Accuracy and Stability	$\pm 0.25\%$, ± 30 ppm/ $^{\circ}$ C
Common-Mode Rejection (DC to 60 Hz)	>80 dB
Common-Mode Voltage Range	± 12 V typical
Post Demodulator Filter	1.0 kHz @ -3 dB
Measurement Range and Resolution	
Range:	± 5 VRMS
Resolution:	50 μ VRMS effective
Excitation	Firmware controlled per card
Frequency	2500, 5000, or 10000 Hz sine wave
Amplitude	3 VRMS
Accuracy	$\pm 0.5\%$ of full scale typical @ 2500 Hz; $\pm 1.0\%$ @ 5000 or 10000 Hz
Current	50 mA max. Over-current/over-temperature protected
Load Regulation	<0.1% of full scale for a load variation of 10% to 100% of full scale load
Temperature Stability	Better than $\pm 0.05\%$ / $^{\circ}$ C
Dimensions	6.5 H x 1.0 W x 12.5 D in (165 x 25.4 x 318 mm)
Weight	0.9 lb (0.4 kg)

Disclaimer

ALL PRODUCTS, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE.

Vishay Precision Group, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "VPG"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

The product specifications do not expand or otherwise modify VPG's terms and conditions of purchase, including but not limited to, the warranty expressed therein.

VPG makes no warranty, representation or guarantee other than as set forth in the terms and conditions of purchase.

To the maximum extent permitted by applicable law, VPG disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Information provided in datasheets and/or specifications may vary from actual results in different applications and performance may vary over time. Statements regarding the suitability of products for certain types of applications are based on VPG's knowledge of typical requirements that are often placed on VPG products. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. You should ensure you have the current version of the relevant information by contacting VPG prior to performing installation or use of the product, such as on our website at vpgsensors.com.

No license, express, implied, or otherwise, to any intellectual property rights is granted by this document, or by any conduct of VPG.

The products shown herein are not designed for use in life-saving or life-sustaining applications unless otherwise expressly indicated. Customers using or selling VPG products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify VPG for any damages arising or resulting from such use or sale. Please contact authorized VPG personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

Copyright Vishay Precision Group, Inc., 2014. All rights reserved.